

**PLOTTER AUDLEY S7000-3 SUBLIMACION**

**Audley 1.8m sublimation printer**



**Features:**

1. Adopt Japan EPSON 5113 Print head, Greatly improve the printing speed
2. Advanced Micro Piezo Technology, realized 1440dpi, perfect printing effect
3. Stable Mute Linear Guide improves the printing speed and resolution
4. Convenient high speed USB interface
5. Fully automatic lifting ink stack, precise alignment. smooth ink absorption
6. Intensive pressing paper roller, prevent the paper running in the wrong direction
7. Developed main board, more convenient to update
8. Heating temperature can be adjusted based on the printing demand

**Model S7000-3**

Print Head	Epson 5113
Number of Printhead	Two
Maximum Print Width	1850mm
Printing Resolution	1440X2880 dpi
Printer color	Gray/Blue
Print Speed Draft:	75m2/h
Production:	55m2/h
Quality	45m2/h

**Casa Central Córdoba** | Silvestre Remonda Nº 364 | 00-54-351-4809161 | Córdoba | Argentina

**Sucursal Buenos Aires** | Perdriel Nº 607 esq. Cortejarena | 00-54-11-43025618/43015660 | Barracas | Buenos Aires | Argentina

**Website:** [www.grafin.com.ar](http://www.grafin.com.ar)

High-resolution		30m2/h
Ink	Type	Sublimation ink Water-based ink
	Color	Double 4 colors(C/M/Y/K)
	Capacity	440ml of each ink cartridge
	Ink supply system	Continuous Ink Supply System
Media	Width	630-1900mm
	Type	Vinyl, Flex, Banner, Wallpaper, PP, Car sticker, Photo paper, Inkjet Light Box,PVC Film, Wallpaper, Reflective film, Textile, fabrics, Canvas, Gum,etc
Printhead Height		1.5-3mm above media adjustable
Drying System	Heating	Front, middle, back three sections heating system, ID temperature controller
	Fanning	Optional
Media adsorption System		several phase of intelligent air draft (Adjustable)
Media Feeding System		Equipped (Max. Media weight 40 kg)
Auto media Take-up System		Optional
Auto cleaning of Printhead		Owning anti-blocking, auto flash & moisturizing function
Clamp		Equipped
Print Interface		USB 2.0
RIP Software		Maintop 5.3/photoprint
Input Power		AC 220V, 50Hz/AC 110V 60Hz
Working environment		Normal temperature 18-35°C, Humidity 40%-70%
Package Size		3120*750*740mm (LxWxH)
Weight		310KG