

Plotter Audley 3.2m DX5 head eco solvent printer





AUDLEY 奧德利
Supplier of solution in professional digital inkjet printing field

INDOOR/OUTDOOR ECO SOLVENT PRINTER

Dual dx7 speed	
High resolution	20m ² /h
Quality	35m ² /h
Standard	45m ² /h
Draft	65m ² /h

Features:

1. Adopt EPSON Dx 5 Printhead, printing color are CMYK, greatly improve the printing speed
2. Advanced MicroPiezo Technology, realized 1440dpi, perfect printing effect
3. Stable Mute linear Guide will improve the printing speed and resolution.
4. Convenience high speed USB interface, plug and play.
5. Automatic lifting ink stack, precision alignment, smooth ink absorption.
6. Intensive pressure roller, printing no skew.
7. Independent research and development, main board upgrade more convenience.
8. Heating Temperature can be control based on printing demand.

Here is the machine video link:

https://youtu.be/Xu9Isy_1gKU

Model	Printhead quantity
ADL-H3200	Two head





Model		ADL-H3200
Print Head		Piezo-electric printhead DX5
Number of Printhead		TWO
Maximum Print Width		3150mm
Printing Resolution		1440X2880 dpi
Printer color		Gray + blue
Print Speed	Draft :	60m2/h
	Production :	36m2/h
	Quality :	30 m2/h
	High-resolution :	16m2/h
Ink	Type	Eco-solvent ink; Water-based ink
	Color	Double4 colors(C/M/Y/K)
	Capacity	440ml of each ink cartridge
	Ink supply system	Continuous Ink Supply System
Media	Width	3200mm
	Type	Vinyl, Flex,Banner,Wallpaper,PP,Car sticker, Photo paper, Inkjet Light Box,PVC film,Wallpaper, Reflective film, Textile, fabrics, Canvas, Gum,etc
Printhead Height		1.5-3mm above media adjustable
Drying System	Heating	Front ,middle ,back three sections heating system,PID temperature controller

	fanning	Optional
	Media adsorption System	Several phase of intelligent air draft(Adjustable)
	Media Feeding System	Equipped (Max. Media weight 40 kg)
	Auto media Take-up System	Optional
	Auto cleaning of Printhead	Owning anti-blocking, auto flash & moisturizing function
	Clamp	Equipped
	Print Interface	USB 2.0
	RIP Software	Maintop 5.3/photoprint
	Input Power	AC 220V,50Hz/AC 110V 60Hz
	Working enviroment	Normal temperature 18-35°C, Humidity 40%-70%
	Package Size	4600mm*1040mm*1470mm (LxWxH)
	Weight	610KG





